



7002 VIBAC® BOPP BOX SEALING TAPE 7002

This carton sealing tape features a PVC (Polyvinyl Chloride) film backing and a natural rubber and resin adhesive. This pressure sensitive tape provides instant adhesion, possesses excellent quick stick properties and sticks to a wide variety of irregular shaped surfaces. It has been specifically formulated to provide great instant adhesion to fiberboard, plastic, glass, metallic, printed and painted surfaces. Excellent for recycled carton sealing in cold temperature environments.

PROPERTIES			
Total thickness micron	52 micron	Total thickness mils	2.100 mils
Business	Industrial Professional	Industry	Bundling Carton Sealing Splicing
Backing Type	BOPP	Backing thickness micron	33 micron
Adhesive type	Natural Rubber	Color	White
Tensile strength kg/cm	4,56 kg/cm	Elongation at break	80 %
Adhesion to steel g/cm	203,9 g/cm	Shear on cardboard	>120 hours
Backing thickness mils	1.300 mils	Tensile strength lb./inch	25.000 lb./inch
Adhesion to steel oz./inch	18 oz./inch	Service Temperature F° (Min / Max)	20/140 °F
Service Temperature C° (Min / Max)	(-7)/60 °C	Available width	150.000 mm 144.000 mm
Available length	990.000 m 914.000 m	Packaging type	jumbo single roll

7002



7000

VIBAC® BOPP BOX SEALING TAPE 7000

This carton sealing tape features a PVC (Polyvinyl Chloride) film backing and a natural rubber and resin adhesive. This pressure sensitive tape provides instant adhesion, possesses excellent quick stick properties and sticks to a wide variety of irregular shaped surfaces. It has been specifically formulated to provide great instant adhesion to fiberboard, plastic, glass, metallic, printed and painted surfaces. Excellent for recycled carton sealing in cold temperature environments.

PROPERTIES			
Total thickness micron	52 micron	Total thickness mils	2.100 mils
Business	Industrial Professional	Industry	Bundling Carton Sealing Splicing
Backing Type	BOPP	Backing thickness micron	33 micron
Adhesive type	Natural Rubber	Color	Clear
Tensile strength kg/cm	4,56 kg/cm	Elongation at break	80 %
Adhesion to steel g/cm	203,9 g/cm	Shear on cardboard	>120 hours
Backing thickness mils	1.300 mils	Tensile strength lb./inch	25.000 lb./inch
Adhesion to steel oz./inch	18 oz./inch	Service Temperature F° (Min / Max)	20/140 °F
Service Temperature C° (Min / Max)	(-7)/60 °C	Available width	150.000 mm 144.000 mm
Available length	990.000 m 914.000 m	Packaging type	jumbo single roll

7000



7001 VIBAC® BOPP BOX SEALING TAPE 7001

This carton sealing tape features a PVC (Polyvinyl Chloride) film backing and a natural rubber and resin adhesive. This pressure sensitive tape provides instant adhesion, possesses excellent quick stick properties and sticks to a wide variety of irregular shaped surfaces. It has been specifically formulated to provide great instant adhesion to fiberboard, plastic, glass, metallic, printed and painted surfaces. Excellent for recycled carton sealing in cold temperature environments.

PROPERTIES			
Total thickness micron	52 micron	Total thickness mils	2.100 mils
Business	Industrial Professional	Industry	Bundling Carton Sealing Splicing
Backing Type	BOPP	Backing thickness micron	33 micron
Adhesive type	Natural Rubber	Color	Tan
Tensile strength kg/cm	4,56 kg/cm	Elongation at break	80 %
Adhesion to steel g/cm	203,9 g/cm	Shear on cardboard	>120 hours
Backing thickness mils	1.300 mils	Tensile strength lb./inch	25.000 lb./inch
Adhesion to steel oz./inch	18 oz./inch	Service Temperature F° (Min / Max)	20/140 °F
Service Temperature C° (Min / Max)	(-7)/60 °C	Available width	150.000 mm 144.000 mm
Available length	990.000 m 914.000 m	Packaging type	jumbo single roll

7001